

1. (Currently Amended) A bone cement plug for fitting into the intramedullary canal within a bone to restrict flow of bone cement during surgery, ~~comprising which comprises:~~

a. ~~a sleeve having a longitudinal axis, whose wall is circumferentially continuous and has an outer surface configured to contact for contacting the wall of the canal, and whose inner surfaces configured to define an internal cavity whose diameter decreases from a distal end to a proximal end, whereat the internal cavity communicates with an opening formed in the outer surface and the longitudinal axis of the sleeve, the sleeve being formed from a deformable material and configured to so that it can be expanded transversely to contact the surface of the canal;~~

~~b. an expander comprising a shaft having a distal end and a transverse portion that extends radially from the distal end of the shaft, the shaft configured to extend through the opening;~~

~~a washer configured to be disposed on the shaft, and having a plurality of radially slots formed therein extending from the outside edge of the washer toward the inside edge thereof; and~~

~~wherein the expander is configured to be movable within which can be drawn through the cavity in a direction generally along the longitudinal axis of the sleeve, from a distal position to a proximal position, whereat the washer contacts the internal cavity to cause the wall of the sleeve to expand transversely to contact the surface of the canal, in which the inner surfaces of the wall converge towards the end of the sleeve towards which the expander is drawn to cause the sleeve to expand to contact the surface of the canal.~~

2. (Currently Amended) ~~The A-bone cement plug of as claimed in claim 1, wherein in which~~ the sleeve has an end wall at the proximal end thereof ~~towards which the expander is drawn to cause the sleeve to expand.~~

3. (Currently Amended) ~~The A-bone cement plug of as claimed in claim 2, wherein in which~~ the end wall of the sleeve is formed as a single body with the wall of the sleeve ~~which contacts the surface of the canal when the sleeve is expanded.~~

4. (Cancelled)

5. (Currently Amended) ~~The A-bone cement plug as claimed in of claim 14, in which wherein~~ the shaft is configured to be frangible at ~~has a defined line of weakness at which it can be broken~~ to allow the transverse portion of the expander to be separated from that portion of the shaft ~~which extends through the opening in the end wall of the sleeve.~~

6-7. (Cancelled)

8. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 14, in which wherein~~ the shaft and transverse portion of the expander are ~~moulded~~ formed as a single component.

9. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 8, in which wherein~~ the shaft and the transverse portion of the expander are formed ~~moulded~~ from a resorbable material.

10. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 1, in which wherein~~ the angle between the inner surface of the wall and the longitudinal axis ~~of the sleeve~~, at the distal end of the sleeve ~~from which the expander is drawn through the cavity in a direction to cause the sleeve to expand transversely~~, is at least about 20-degrees.

11. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 1, in which wherein~~ the angle between the inner surface of the wall and the longitudinal axis ~~of the sleeve~~, at the distal end of the sleeve ~~from which the expander is drawn through the cavity in a direction to cause the sleeve to expand transversely~~, is not more than about 50-degrees.

12. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 1, in which wherein~~ the outer surface of the sleeve has surface features to promote engagement with the bone surface of the intramedullary canal.

13. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 1, in which wherein~~ the sleeve has at least one indent in the surface which defines the internal cavity, the indent extending around the internal cavity approximately in a plane that ~~which~~ is perpendicular to the axis of the sleeve.

14. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 1, in which wherein~~ the hardness of the material of the sleeve is at least about 30 Shore A.

15. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 1, in which wherein~~ the hardness of the material of the sleeve is not more than about 75 Shore A.

16. (Currently Amended) ~~A-The bone cement plug as claimed in of claim 1, in which wherein~~ the sleeve is formed from a resorbable material.

17. (Currently Amended) An assembly for use in orthopaedic surgery, comprising: which  
~~comprises~~ a bone cement plug ~~as claimed in~~ claim 1 and an instrument for locating the plug in  
the intramedullary canal within a bone.

18. (Currently Amended) ~~The An-assembly as claimed in~~ claim 17, ~~in which~~ wherein the  
expander comprises a shaft that ~~which~~ extends generally along the longitudinal sleeve-axis, and  
~~in which~~ wherein the instrument includes a socket for engaging the shaft on the expander.

19. (Currently Amended) ~~The An-assembly as claimed in~~ claim 17, which includes a drive  
unit by which the expander can be drawn into the sleeve to cause ~~it~~ the expander to move from  
the distal position to the proximal position ~~to expand transversely~~.

20. (New) A bone cement plug for fitting into the intramedullary canal within a bone to restrict  
flow of bone cement during surgery, comprising:

a sleeve having an outer surface configured to contact the wall of the canal, an internal  
cavity and being formed from a deformable material;

an expander comprising a shaft having a distal end and a transverse portion that extends  
radially from the distal end of the shaft; and

a washer configured to be disposed on the shaft, and having a plurality of radially slots  
formed therein extending from the outside edge of the washer toward the inside edge thereof,

wherein the expander is movable within the cavity from a distal position to a proximal  
position, whereat the washer contacts the internal cavity to cause the wall of the sleeve to expand  
transversely to contact the surface of the canal.